

## (EU) No 1254/2014 data

Trade mark	Komfovent
Model	DOMEKT-R-200-V-E-R1-M5/M5-C4-L/A
SEC (climate zone 1 / 2 / 3)*	-78,1 / -36,4 / -12,5 kWh/m²
Typology	Bidirectional
Drive type	Variable speed drive
Heat recovery system	Regenerative
Thermal efficiency	80 %
Maximum flow rate	258 m³/h
Fan drive electric power	66 W
Casing sound power level	43 dBA
Reference flow rate	0,05 m³/s
Reference pressure difference	50 Pa
SPI	0,32 W/(m³/h)
Control factor	0,85
Control typology	Central demand control
Maximum external leakage	< 1 %
Carry over	< 0,5 %
Filter warning	When filter gets dirty, the unit control panel notifies the user about the need to change it. Dirty filters cause increased energy consumption, which decreases performance and energy efficiency of the unit, so it is very important to change the filters regularly.
Instructions	<a href="http://www.komfovent.com">www.komfovent.com</a>
AEC (climate zone 1 / 2 / 3)*	286,4 / 286,4 / 286,4 kWh/annum
AHS (climate zone 1 / 2 / 3)*	85,2 / 43,6 / 19,7 kWh/annum
*Climate zones 1 / 2 / 3	1 - cold / 2 - average / 3 - warm

